



BACK-UP ALARMS



MULTI-FREQUENCY™ Surface Mount

Multi-Frequency back-up alarms provide a solution to potential noise pollution created by conventional tonal back-up alarms in confined or densely populated work areas. These Multi-Frequency alarms maintain a safe warning signal for those in the danger zone of backing vehicles while minimizing disturbance to work site neighbors. Multi-Frequency alarms operate by emitting sound at multiple frequencies attenuated above 4000Hz.

Models

PART NO.	TYPE	VDC	dB(A)	AMPS	APPROVALS
EA5050	MFA	12-24	87	0.4	SAE Type D, RCM, AMECA
EA5200	MFA	12-24	97	1.0	SAE Type C, RCM, AMECA
EA5200-APT2	Aptiv Tech. 2-pin connector	12-24	97	1.0	SAE Type C, RCM, AMECA
EA6100	MFA	12-24	97	0.7	SAE Type C
EA7020	MFA	12-24	102	0.6	SAE Type F, AMECA, IP66
EA7070	MFA	12-24	107	0.8	SAE Type B, AMECA, IP66
EA9070	MFA/Smart	12-24	87-107	0.9	SAE Type F, IP66
EA9724	MFA/Smart	12-24	77-97	0.7	SAE Type F
EA9724-DEU	MFA/Smart	12-24	77-97	0.7	SAE Type F

Design Features

- Emits sound at multiple frequencies attenuated above 4000Hz
- Warning signal is more directional and perceived to dissipate quicker than pure tone
- Smart Alarm models adjust output to 5dB above surrounding noise
- Sealed in epoxy for protection against dust, moisture, and vibration
- Temperature Range: -40°F to +185°F (-40°C to +85°C)

Alarm Specifications

Reinforced nylon housing / 2-16 AWG wire connection

Recommended mounting bolt: 1/4" Grade 5 (5050 & 5200), 3/8" Grade 5 (6100, 7020, 7070, 9070 & 9724)

Recommended washer: 1/4" Type A, Series A or W (5050 & 5200), 3/8" Type A, Series N or W (6100, 7020, 7070, 9070 & 9724)

Recommended mounting torque: 276 in. lbs. (6100, 7020, 7070, 9070 & 9724)

Recommended mounting torque: 76 in. lbs. (5050 & 5200)

Warranty:

2 Years: EA5050, EA5200, EA5200-APT2

ECCOLIFE™: EA6100, EA7020, EA7070, EA9070, EA9724



BACK-UP ALARMS



MULTI-FREQUENCY Surface Mount

Multi-Frequency back-up alarms provides a solution to potential noise pollution created by conventional tonal back-up alarms in confined or densely populated work areas. Those Multi-Frequency alarms maintain a safe warning signal for those in the danger zone of backing vehicles while minimizing disturbance to work site neighbors. Multi-Frequency alarms operate by emitting sound at multiple frequencies attenuated above 4000Hz. In addition, the reverse mounted speaker design of the EA6100, EA9724 and EA9780, and the driver technology used in the EA7020, EA7070 and EA9070, models extends the life expectancy of the alarm, so much so, that a life of the vehicle warranty is offered.

Alarm Specifications

Reinforced nylon housing / 2-16 AWG wire connection

Recommended mounting bolt: 3/8" Grade 5

Recommended washer: 3/8" Type A, Series N or W

Recommended mounting torque: 276 in. lbs.

Models

PART NO.	TYPE	VDC	dB(A)	AMPS
EA6100	MFA	12-24	97	0.7
EA7020	MFA	12-24	102	0.6
EA7070	MFA	12-24	107	0.8
EA9070	MFA/Smart	12-24	87-107	0.9
EA9724	MFA/Smart	12-24	77-97	0.7

Features and Benefits

- Emits sound at multiple frequencies attenuated above 4000Hz
- Warning signal is more directional and perceived to dissipate quicker than pure tone
- Smart Alarm models adjust output to 5dB above surrounding noise
- Sealed in epoxy for protection against dust, moisture, and vibration
- Temperature Range: -40°F to +185°F (-40°C to +85°C)